



# EVOline® Square80



## EVOline® Square80

Many desks have pre-made openings for cables with a diameter of 80mm. EVOline Square80 fits into this standard opening combining a power socket, a USB charging socket, and a network connection.

In its Qi version EVOline Square80 offers an additional inductive charging surface integrated into the cover, for charging all Qi capable mobile phones per WPC Standard 1.1.



Description Picture Specification Order number

#### **EVOline Square80**

Installation for surface thickness of up to 50 mm.

Mounting hole Ø 80 mm.

Configuration:
1 power outlet, VDE-compliant,
16 A, contact-protected,
1 x USB Type A Charger, charging function only - ideal for charging of USB-chargeable devices, i.e.

Apple iPhones, iPads, iPods\*\*,

Fixed supply cable 3.0 m with angled plug.

Tablets, Smart phones,

MP3 Players.

For the complete cable management solution, we recommend EVOline WireLane and EVOline Bridge to cover exposed cables. Available to order separately.

## International versions available upon request.

The USB charging function cannot be guaranteed due to the multitude of manufacturers and devices on the market

### \* For all Qi-compliant mobile phones with WPC standard 1.1

\*\* ™ Apple Computer Inc.

Become a co-designer and select your country-specific EVOline Square80.





#### Without Qi charging function

Cover and housing black

With CAT 6 socket, 3,0 m cable and plug 1592 7000 0100

With CAT6 pull-out patch cable 3.0 m 1592 7000 0200

Without data 1592 7000 0300

Cover and housing white With CAT 6 socket, 3,0 m cable and plug

1592 7000 1900

With CAT6 pull-out patch cable  $3.0\ \mathrm{m}$ 

1592 7000 2000

Without data 1593

1592 7000 2100

Cover in stainless steel optics, housing in black With CAT 6 socket, 3,0 m

1592 7000 3100

With CAT6 pull-out patch cable 3.0 m

1592 7000 3200

Without data

cable and plug

1592 7000 3300

#### With Qi charging function\*

Cover and housing black With CAT 6 socket, 3,0 m cable and plug

1592 7000 0400

With CAT6 pull-out patch cable  $3.0\ \mathrm{m}$ 

1592 7000 0500

Without data

1592 7000 0600

Cover and housing white With CAT 6 socket, 3,0 m cable and plug

1592 7000 2200

With CAT6 pull-out patch cable

3.0 m

1592 7000 2300

Without data

1592 7000 2400

Cover in stainless steel optics, housing in black

With CAT 6 socket, 3,0 m cable and plug

1592 7000 3400

With CAT6 pull-out patch cable

3.0 m

1592 7000 3500

Without data

1592 7000 3600