

A black, cylindrical smart kitchen socket is shown in its retracted position on a dark wooden table. The socket has a standard AC outlet on top, a USB-C port, and a wireless charging pad. A white circle highlights the front panel. In the background, a wooden chair and a bowl of fresh vegetables are visible.

ELEVATOR 2

RELAX COOK ENJOY WOW

Power up with a simple touch

ELEVATOR 2 is the smart, retractable socket solution for modern kitchens. With a single tap, the unit lifts from the worktop when power is needed – and disappears flush when it's not. A refined evolution of the classic ELEVATOR, now with added comfort and advanced technology.

Whether you're charging via USB-C/C with up to 45 watts or wirelessly via Qi2 and Magnetic Power Profile, your devices power up efficiently – even when the unit is retracted.

With IP54 protection, ELEVATOR 2 is splash-proof and safe to use near water. Premium surfaces and flush installation give your kitchen a clean, elegant look.

Best of all, it fits in a standard 80mm cut-out – ideal for both new installations and retrofits.

Advantages

- Retractable kitchen socket with soft opening
- USB-C socket with 45-watt charging power
- Wireless Charging with Qi2 and MPP
- IP54-certified splash-water protection
- 80mm standard cut-out



Find out more:
<http://bachmann.com/elevator-2>

ELEVATOR 2

- Material: Profile: Aluminium | Socket: Plastic
- Mounting depth (without cable): 180 mm
- Tabletop thickness: 10 – 60 mm



Stainless steel look | Power input: 2.0m cable with ferrules and mounting plug, included

| | | | | | | | | | | |
|-----------|---|---|---|--|---------|---|---|-----|----------|----------------|
| BM0020484 | 2 | | | | | | | 90° | | 283 x Ø 114 mm |
| BM0020489 | 1 | | | | | | 2 | 90° | | 283 x Ø 114 mm |
| BM0020491 | | | 2 | | | | | 90° | | 283 x Ø 114 mm |
| BM0020494 | | | | | | 2 | | 50° | | 303 x Ø 114 mm |
| BM0020495 | | | | | 2 (T23) | | | 0° | | 303 x Ø 114 mm |
| BM0020496 | | 2 | | | | | | 0° | | 303 x Ø 114 mm |
| BM0020570 | 1 | | | | | | | 90° | C/C 45 W | 283 x Ø 114 mm |
| BM0020571 | | | 1 | | | | | 90° | C/C 45 W | 283 x Ø 114 mm |
| BM0020572 | | | | | | 1 | | 50° | C/C 45 W | 283 x Ø 114 mm |
| BM0020573 | | | | | 1 (T13) | | | 0° | C/C 45 W | 283 x Ø 114 mm |
| BM0020574 | | 1 | | | | | | 0° | C/C 45 W | 303 x Ø 114 mm |

Matt black | Power input: 0.5m cable and ISV

| | | | | | | | | | | |
|-----------|---|---|---|--|---------|---|---|-----|----------|----------------|
| BM0020503 | 2 | | | | | | | 90° | | 283 x Ø 114 mm |
| BM0020504 | 1 | | | | | | 2 | 90° | | 283 x Ø 114 mm |
| BM0020505 | | | 2 | | | | | 90° | | 283 x Ø 114 mm |
| BM0020506 | | | | | | 2 | | 50° | | 283 x Ø 114 mm |
| BM0020507 | | | | | 2 (T23) | | | 0° | | 283 x Ø 114 mm |
| BM0020508 | | 2 | | | | | | 0° | | 283 x Ø 114 mm |
| BM0020580 | 1 | | | | | | | 90° | C/C 45 W | 283 x Ø 114 mm |
| BM0020581 | | | 1 | | | | | 90° | C/C 45 W | 283 x Ø 114 mm |
| BM0020582 | | | | | | 1 | | 50° | C/C 45 W | 283 x Ø 114 mm |
| BM0020583 | | | | | 1 (T13) | | | 0° | C/C 45 W | 283 x Ø 114 mm |
| BM0020584 | | 1 | | | | | | 0° | C/C 45 W | 283 x Ø 114 mm |

Matt black | Power input: 2.0m cable with ferrules and mounting plug, included

| | | | | | | | | | | |
|-----------|---|---|---|--|---------|---|---|-----|----------|----------------|
| BM0020497 | 2 | | | | | | | 90° | | 283 x Ø 114 mm |
| BM0020498 | 1 | | | | | | 2 | 90° | | 283 x Ø 114 mm |
| BM0020499 | | | 2 | | | | | 90° | | 283 x Ø 114 mm |
| BM0020500 | | | | | | 2 | | 50° | | 283 x Ø 114 mm |
| BM0020501 | | | | | 2 (T23) | | | 0° | | 283 x Ø 114 mm |
| BM0020502 | | 2 | | | | | | 0° | | 283 x Ø 114 mm |
| BM0020575 | 1 | | | | | | | 90° | C/C 45 W | 283 x Ø 114 mm |
| BM0020576 | | | 1 | | | | | 90° | C/C 45 W | 283 x Ø 114 mm |
| BM0020577 | | | | | | 1 | | 50° | C/C 45 W | 283 x Ø 114 mm |
| BM0020578 | | | | | 1 (T13) | | | 0° | C/C 45 W | 283 x Ø 114 mm |
| BM0020579 | | 1 | | | | | | 0° | C/C 45 W | 283 x Ø 114 mm |

Matt black | Wireless Charging with Qi2 and MPP | Power input: 0.5 m cable and ISV

| | | | | | | | | | | |
|-----------|---|---|---|--|---------|---|--|-----|--------|----------------|
| BM0020530 | 1 | | | | | | | 90° | C 45 W | 283 x Ø 114 mm |
| BM0020531 | | | 1 | | | | | 90° | C 45 W | 283 x Ø 114 mm |
| BM0020532 | | | | | | 1 | | 50° | C 45 W | 283 x Ø 114 mm |
| BM0020534 | | | | | 1 (T13) | | | 0° | C 45 W | 283 x Ø 114 mm |
| BM0020537 | | 1 | | | | | | 0° | C 45 W | 283 x Ø 114 mm |

Matt black | Wireless Charging with Qi2 and MPP | Power input: 2.0 m cable with ferrules and mounting plug, included

| | | | | | | | | | | |
|-----------|---|---|---|--|---------|---|--|-----|--------|----------------|
| BM0020509 | 1 | | | | | | | 90° | C 45 W | 283 x Ø 114 mm |
| BM0020510 | | | 1 | | | | | 90° | C 45 W | 283 x Ø 114 mm |
| BM0020521 | | | | | | 1 | | 50° | C 45 W | 283 x Ø 114 mm |
| BM0020523 | | | | | 1 (T13) | | | 0° | C 45 W | 283 x Ø 114 mm |
| BM0020527 | | 1 | | | | | | 0° | C 45 W | 283 x Ø 114 mm |

